

# ECOSOFT ROBUST REVERSE OSMOSIS SYSTEM



**Application:** cafes, restaurants, apartments, private houses, pharmacies, laboratories.

**Description:** compact high-capacity direct flow reverse osmosis system.

**Filtration technology:**

- Sediment PP 5 micron filter
- GAC activated carbon filter
- RO membranes (3 x Filmtec TW30-1812-100)
- Coconut shell carbon filter

**Key features:**

1. Consistent and high flow rate due to advanced system architecture.
2. Delicious water due to Filmtec membranes and high quality activated carbon filters.
3. Original and compact design.
4. Standard replacement filter and membranes.
5. Easy-to-use connections.
6. Designed for tankless operation.
7. CE marked and confirmed to be safe in accordance with EC New Approach Directives.

**Specifications:**

Code	Peak flow capacity*, gph	Water consumption, gph	Power supply	Power consumption, kW	Dimensions, H x D x W, inch
ROBUST	15.8	31.7	110 V, 60 Hz	0.08	16.5 x 8.7 x 16.7

\* At feed water temperature 77 °F, feed water TDS 1000 mg/L.  
Recommended average flow capacity is 135 GPD.

**Components:**

- Robust water purification system
- Connection fitting pack
- Service wrench
- Instruction manual